



M43

Access Control

PIN only reader

-
- Group code level
 - PIN code function
 - Sturdy construction for outdoor and indoor use

In a SiPass Intro system, the M43 is used primarily in two situations when you only require the group code level in the system, or when you want to add PIN code functionality to a door that already has a card-only reader installed.

Technical data

M43	
System compatibility	SiPass Entro Lite, SiPass Entro
Interface to controller	BC-Link
Operating voltage	12 to 24 VDC, powered from door controller
Current consumption	27 mA @ 12 VDC 39 mA @ 24 VDC
Inputs	Tamper switch for internal alarm
Tamper switch	Yes
Indicators	3 x LED (red/yellow/green) 1 x Buzzer
Keypad	Stainless steel keys 0-9, A, B
Operating temperature	-35 to +50 °C
Environment	Indoor or outdoor use
IP rating	IP54
Housing	Cast metal with stainless steel keys and security lock.
Colour	Grey
Dimensions (W x H x D)	80 x 140 x 40 mm
Approval	CE
Accessories	SH2 rain cover IS391 spy-proof cover BB3 flush-mounting kit

Details for ordering

Type	Part no	Designation	Weight
M43	S24246-F8400-A1	PIN only reader	0.70 kg

Issued by

Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
D-76181 Karlsruhe
www.buildingtechnologies.siemens.com

© 2009 Copyright by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
Data and design subject to change without notice.
Supply subject to availability.